Power tool Plastic tie wraps clamping







Large tie wraps

Clamping: 2 clamping levels

Tension : from 39.34 to 66.77 lbs (175 - 297 N) Tie wraps : from 0.18 - 0.30 in (4.8 to 7.6 mm)



Battery operated



Narrow and rotative head







Autonomy > 8h, eq. 3200 tie wraps Indicators battery



Narrow and 360° rotative head Adjustable and repeatable clamping



Resistant to floor falls Easy maintenance

ADT Tools in videos



Alpes DEIS - 74970 Marignier - FRANCE
Phone : +33 (0)4 50 89 24 00
Email : adt-sales@alpes-deis.fr

Power tool Plastic tie wraps clamping



Product information

Powered clamping tool for plastic tie wraps facilitating the tightening operation by its **ergonomics** and **features improving the process**. Better the process and tightening thanks to its **high repeatability**, its **fast cycle** and its **accessibility**. Prevents from Musculoskeletal Disorders (MSD) and scratches thanks to the **clean cut** and **no effort needed** from the operator.

Already used in:













Product characteristics

Sales reference	ADT120-PROD	GGY SAD
Dimensions (H x L x W)	195 mm (7.68 in) x 270 mm (10.6 in) x 70 mm (2.75 in)	To the state of th
Head characteristics	Narrow and 360° rotative head, flush cut of the tie wrap	(6
Material	PA6 composite charged in glass fiber 30%, drop resistance	6
Clamping force	Adjustable : 2 levels of clamping from 39.34 to 66.77 lbs (175 - 297 N)	(nr)
Tie wraps width	0.18 to 0.30 in (4.8 - 7.6 mm) - other widths, see Product Range	
Tie wraps type	e wraps type Compatible with Advanced Cable Ties, HellermannTyton, ABB, Panduit, Legrand.	

Usage characteristics

Usability	< 1.9 lbs (900g) (battery included) Ambidextrous tool, center of gravity in the handle
Autonomy	> 8h, equivalent to the clamping of 3200 tie wraps 3 levels battery indicator
Maintenance	Easy product maintenance (more information in the user manual)

Accessories

Rechargeable battery	Lithium-lon, 11.25V / 2.95Ah, recyclable	CC J
Battery charger	Universal: 110 - 240 Vac, 50/60Hz Available in United-States, Europe, United-Kingdom, Australia versions	
ADT 20 blades kit	20 cutting blades	
ADT maintenance kit	1 ADT-120 head, 1 head disassembly tool	
ADT measure certificate	Characterization of clamping forces	
Suspension hook	Usable on fixed work station	

Product Range

ADT-50	Tie wraps width: 0.09 - 0.18 in (2.4 - 4.8 mm) Clamping force: 14.61 - 56.20 lbs (65 - 250 N) - 8 positions	
ADT-120	Tie wraps width: 0.18 - 0.30 in (4.8 - 7.6 mm) Clamping force: 39.34 - 66.77 lbs (175 - 297 N) - 2 positions	I
ADT-120L	Tie wraps width: 0.18 - 0.30 in (4.8 - 7.6 mm) Clamping force: 14.61 - 56.20 lbs (65 - 250 N) - 8 positions	

os

© Contact Alpes DEIS - 74970 Marignier - FRANCE Phone : +33 (0)4 50 89 24 00 Email : adt-sales@alpes-deis.fr