# **Power tool** Plastic tie wraps clamping









Small tie wraps The information, photographs, drawings and logos in this document are protected by industrial and/or intellectual property fights. Any reproduction, total or partial, of one or more of its components, by any process whatsoever, is strictly prohibited and constitutes an infringement

Clamping: 8 levels of clamping

: from 14.61 to 56.20 lbs (65 - 250 N) Tension Tie wrap: from 0.09 to 0.18 in (2.4 - 4.8 mm)



Battery operated



Narrow and rotative head





Weigth < 900g Reduction of MSD



Autonomy > 8h, eq. 3200 tie wraps Indicators battery



Narrow and 360° rotative head Adjustable and repeatable clamping



Resistant to floor falls Easy maintenance



Alpes DEIS - 74970 Marignier - FRANCE Phone: +33 (0)4 50 89 24 00 Contact

Email: adt-sales@alpes-deis.fr

# Power tool Plastic tie wraps clamping



#### **Product information**

**Powered clamping tool** for plastic tie wraps facilitating the tightening operation by its **ergonomics** and **features improving the process**. Better the process and tightening thanks to its **high repeatability**, its **fast cycle** and its **accessibility**. Prevents from Musculoskeletal Disorders (MSD) and scratches thanks to the **clean cut** and **no effort needed** from the operator.

Already used in:













#### **Product characteristics**

Sales reference	ADT50-PROD	GEGY SAV
Dimensions (H x L x W)	195 mm (7.68 in) x 270 mm (10.6 in) x 70 mm (2.75 in)	To the second se
Head characteristics	Narrow and 360° rotative head, flush cut of the tie wrap	(6
Material	PA6 composite charged in glass fiber 30%, drop resistance	(6
Clamping force	Adjustable: 8 levels of clamping from 14.61 to 56.20 lbs (65 - 250 N)	(ŮL)
Tie wraps width	0.09 to 0.18 in (2.4 - 4.8 mm) - other widths, see Product Range	
Tie wraps type	Compatible with Advanced Cable Ties, HellermannTyton, ABB, Panduit, Legrand	

## **Usage characteristics**

Usability	< 1.9 lbs (900g) (battery included) Ambidextrous tool, center of gravity in the handle
Autonomy	> 8h, equivalent to the clamping of 3200 tie wraps 3 levels battery indicator
Maintenance	Easy product maintenance (more information in the user manual)

#### **Accessories**

Rechargeable battery	Lithium-Ion, 11.25V / 2.95Ah, recyclable	Comment of
Battery charger	Universal: 110 - 240 Vac, 50/60Hz Available in United-States, Europe, United-Kingdom, Australia versions	
ADT 20 blades kit	20 cutting blades	
ADT maintenance kit	1 ADT-50 head, 1 head disassembly tool	
ADT measure certificate	Characterization of clamping forces	
Suspension hook	Usable on fixed work station	Ů.

### **Product Range**

ADT-50	Tie wraps width: 0.09 - 0.18 in (2.4 - 4.8 mm) Clamping force: 14.61 - 56.20 lbs (65 - 250 N) - 8 positions	
ADT-120	Tie wraps width: 0.18 - 0.30 in (4.8 - 7.6 mm) Clamping force: 39.34 - 66.77 lbs (175 - 297 N) - 2 positions	
ADT-120L	Tie wraps width: 0.18 - 0.30 in (4.8 - 7.6 mm) Clamping force: 14.61 - 56.20 lbs (65 - 250 N) - 8 positions	

ADT Tools in videos



Contact

Alpes DEIS - 74970 Marignier - FRANCE Phone : +33 (0)4 50 89 24 00 Email : adt-sales@alpes-deis.fr